

# KALKO

Strong, reliable and professional  
Spreading width up to 16 m



## FEATURES

Spreading width with both augers: 6 + 6 m

40 openings per 6 m auger

Auger spiral: Ø 15 cm

Height of the auger from the ground: 87 cm

Possibility of removing the covers for cleaning inside the spirals

Capacity up to 5 t/ha to 6 km/h

Capacity up to 3 t/ha to 10 Km/h

PVC double windproof auger cover

Spreading width with discs: up to 16 m

## BELT CONVEYOR

The belt conveyor is driven by a hydraulic motor equipped with a speed sensor with a proportional valve controlled by the computer.

- Width: 800 mm

## HOPPER SHAPE FOR PROTECTION

Robust angular hopper edges for protection from accidental contact with the bucket scraper during product loading.

## OPTIONS

- Hopper cover
- ISOBUS SYSTEM kit (\*)

## ALL MODELS ARE EQUIPPED WITH

- **Independent hydraulic circuit**
- Varnished steel hopper
- Hydraulic opening/closing of fertilizer flow
- 600/55 R 26,5 tyres
- Tail lights
- Line holder
- Pneumatic brakes
- Mudguards
- **Internal deflectors**
- Chain harrows
- **Steering rear axle**
- **Hydraulic augers 12 m (6 m x 2)**
- **Discs for spreading lime up to 16 m**
- Document holder
- **Computer**
- Wheel speed sensor
- Electrical wiring
- Hydraulic belt control
- Belt speed sensor
- Hydraulic discs drive
- Disc speed sensor

Models	Capacity (m <sup>3</sup> )	Max. load (kg)	Weight (kg)	Length (cm)	Width (cm)	Height (cm)	Tractor Power (HP)
KALKO 10000	9.5	20 000	5750	764	284	277	150
KALKO 14000	13.8	20 000	5920	764	284	317	160

(\*) Available from season 2015