Twin disc centrifugal spreader













MONEY SAVING THROUGH WEIGHING CONTROL!

AGREX S.p.A. proudly presents the fertilizer spreader with **integrated weighing KYLO SYSTEM**.

The **KYLO SYSTEM** allows to gear automatically the opening of the dosing gates up to the speed of the tractor and the peculiarities of the fertilizer's flow.

More respect of the environment and economic savings are the results of the extraordinary precision in spreading and the easy use of the **KYLO SYSTEM**.

The available models are:

• KYLO: Capacity from 1500 to 3000 liters

YOUR BENEFITS

- A strong structured frame with on-line weighing up to a load of 3000 kg. The weighing system is integrated in the fertilizer spreader frame
- For working on slopes there is no lateral stress of the weighing cell because hopper frame and distribution are a single body
- The easy setting of spreading quantity and spreading width increase working comfort and security
- · GPS adaptable
- All mechanical and electronic security devices are made according to EU safety regulations
- The very simple maintenance is reduced to a minimum

CX15 CX30



TRAILER mod. CX15 For XPS models

Weight	260 kg
Load on hook	150 kg
Total weight when fully loaded	2.000 kg
Maximum load	1.500 kg
Wheel size	10,0/75-15,3''
Maximum speed	40 km/h
Lenght	275 cm
Width	210 cm
Height	100 cm

All models are equipped with: Trailer rear lights – PTO shaft – Chocks



TRAILER mod. CX30 For XDI and KYLO models

Weight	420 kg
Load on hook	500 kg
Total weight when fully loaded	3.850 kg
Maximum load	3.000 kg
Wheel size	15,0/55-17"
Maximum speed	40 km/h
Lenght	310 cm
Width	227 cm
Height	210 cm

All models are equipped with: Trailer rear lights — PTO shaft — Chocks









The **AVC painting process** is an advanced technique that makes the treated elements very resistant to corrosion.

AGREX uses this method to paint its fertilizer-spreaders in order to offer to the end user durable and strong machines that are resistant to high corrosion coefficient of the fertilizers.

ADVANTAGES:

- · Better resistance to corrosion
- Uniform surface coating of all the parts
- Smooth surface
- In compliance with the European and USA environmental standards





